

BIAS EARTHMOVER - LOADER TYRES (WIDE BASE)

Part No.	Tyre Size	Ply Rating	Speed Symbol	Type	Pattern	Section Width		Overall Diameter		Max. Speed		Infl. Pressure		Max. Load		Standard Rim	Tyre Valve	Tread Depth (mm)	Tread Depth (32nds)
						mm	ins	mm	ins	Km/h	mph	kPa	psi	kg	Lbs				
A1AGO24	17.5 - 25	16	B/A2	TT	L-3	445	17.5	1350	53.1	50/*10	30/*5	300/*475	44/*69	4250/*7300	9350/*16100	14.00	Z1-01-8	30	37.8
A1AGO24	23.5 - 25	20	B/A2	TT	L-3	595	23.4	1615	63.6	50/*10	30/*5	300/*375	44/*54	7300/*10900	16100/*24000	19.5	Z1-01-8	35	44.1

CARACTERISTICAS

L-3

- ▶ Carcasa diagonal formada por hilos de alta resistencia.
- ▶ La banda de rodamiento esta formada por resaltos en forma de "S" con un refuerzo en zigzag en el centro, propio para un trabajo en rocas y otras condiciones exigentes.
- ▶ Compuestos de caucho especial para brindar seguridad y duración máxima a un costo operacional mínimo.



L-3